



NU-T-LINK™

POLYURETHANE REINFORCED CLASSICAL SECTION OPEN END LINK V-BELT

Designed for rapid installation in an assortment of lengths and operating conditions.

CONSTRUCTION + SPECIFICATIONS

- Excellent substitute for emergency repairs and quick belt replacement in difficult/tight assembly areas.

BELT IDENTIFICATION





NTL/A
NTL - Nu-T-Link
A - Cross Section
Standard length: 50' Reels
The studs are color coded: O - Red; A - Silver; B - Green; C - Blue

Available Stock Sizes
 O, A, B, C

FEATURES + BENEFITS

- Suitable alternative to standard belts on all industrial applications and particularly suited to drives requiring link belting for ease of installation.
- Color-coded studs make for easy identification and installation.
- Orangle Polyurethane/Polyester composite resists oil, water, chemicals and heat.
- May be assembled in an assortment of lengths to fit multiple drive configurations.
- Not for use with backside idler applications.
- Does not meet RMA static conductivity requirements.
- Operating temperature range: -40°C/-40°F to +100°C/212°F.

Belt Identification Chart

<p>3/8"</p>  <p>O</p> <p>SECTION</p>	<p>1/2"</p>  <p>A</p> <p>SECTION</p>	<p>21/32"</p>  <p>B</p> <p>SECTION</p>	<p>7/8"</p>  <p>C</p> <p>SECTION</p>
--	--	--	--

